

IB639

2MP Bullet Camera



Technical Specifications

Camera Features


Image sensor	1/3.1" Progressive CMOS
Resolution	SD:1280 x 720 HD: 1920 x 1080
Lens Types	Fixed-focal
Focal Length	f = 2.8 mm
Aperture	F2.0
Iris	Fixed iris
Field of View	116° (Horizontal) 65° (Vertical) 140° (Diagonal)
Camera Movement	Tilt: 90° Rotate:180°
Shutter Speed	1/5 sec. to 1/32,000 sec.
Day/Night	Yes
IR Cut Filter	Yes
IR Range	30 meters
WDR Technology	WDR Enhanced
Minimum Illumination	0.08 lux @ F2.0 (Color) <0.005 lux @ F2.0 (B/W) 0 lux with IR illumination on
Onboard Storage	MicroSD/SDHC/SDXC card slot (Built-in 128GB industrial SDCard)

Standard Video Settings

Frame Rate	15FPS
Video Streaming Settings	HD Video 1920 x 1080@15fps 600Kbps upload SD Video 1280 x 720@15fps 200Kbps upload

Standard Audio Settings

Audio	-
Interface	-
Effective Range	-



Power and Network

Power input	IEEE 802.3af Class 0 PoE, DC 12V (Simultaneous Power Redundancy Supported)
Power Consumption	PoE: Max. 6.49W/4W (IR on/off) DC 12V: Max. 5.1W/3.4W (IR on/off)
Connectivity	RJ-45 cable connector for 10/100 Mbps PoE network connection
RTSP	WebRTC, ARP, DHCP, DNS, HTTP, HTTPS, ICMP, IPv4, IPv6, NTP, QoS (CoS/DSCP), RTSP/RTP/RTCP, SSL, TCP/IP, TLS 1.2, UDP
Users	Up to 4 clients *Live viewing for 4 clients *live viewing up to 2 clients and playback 2 clients)
Security	Signed firmware HTTPS/TLS encryption Video encryption
Interface	10 Base-T/100 Base-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.

General

Operating Temperature	Starting Temperature: -30°C ~ 50°C (-22°F ~ 122°F) Working Temperature: -30°C ~ 55°C (-22°F ~ 131°F) (IR off) -30°C ~ 50°C (-22°F ~ 122°F) (IR on)
Humidity	95% RH (non-condensing)
Certifications	EMC: CE (EN55032 Class B, EN55035), FCC (FCC Part 15 Subpart B Class B), ICES-003 issue 7, RCM (AS/NZS CISPR 32 Class B), VCCI (VCCI-CISPR 32 Class B); Safety: UL (UL 62368-1), CB (IEC/EN 62368-1, IEC/EN 62471, IEC/EN 60950-22); Environment: IK10 (IEC 62262), IP66 (IEC 60529)
Warranty	Up to 10 years (Depends on license type)
Included Accessories	Quick installation guide, alignment sticker, screw pack, cable gland

Mechanical

Weight	671g
Dimensions	Ø 91.1 x 181.5 mm
Body	Metal

AI Analytics

Audio detection	-
Tampering detection	Yes
Application	Intrusion detection, Line crossing detection, Loitering detection, Unattended object detection, Missing object detection
AI Hub with xPro License	Deep search, Scene search, Think search, Event insight
Application available with license	-