



Test report No: 2410697R-0E3012150009-A

Canada TEST REPORT

Product Name	Network Camera
Trademark	VIVOTEK
Model and /or type reference	FD9383-HV, FD833-HV
Applicant's name / address	VIVOTEK INC. / 6F, No.192, Lien-Cheng Rd., Chung-Ho, New Taipei City, Taiwan, R.O.C.
Manufacturer's name / address	VIVOTEK INC. / 6F, No.192, Lien-Cheng Rd., Chung-Ho, New Taipei City, Taiwan, R.O.C.
Test method requested, standard	ICES-003 Issue 7:2020, Class A
Verdict Summary	IN COMPLIANCE
Documented By (Senior Adm. Specialist / Rita Huang)	
Approved By (Director / Vincent Lin)	
Date of Report	2024/01/24
Date of Issue	2024/04/17
Report No.	2410697R-0E3012150009-A
Report Version	V1.0

INDEX

Description	Page
1. General Information	5
1.1. EUT Description.....	5
1.2. Mode of Operation	6
1.3. Configuration & Details of Tested System	7
1.4. EUT Exercise Software.....	8
2. Technical Test.....	9
2.1. Summary of Test Result.....	9
2.2. List of Test Equipment	10
2.3. Measurement Uncertainty.....	11
2.4. Test Environment	12
3. Radiated Emission	13
3.1. Test Specification	13
3.2. Test Setup.....	13
3.3. Limit	14
3.4. Test Procedure.....	15
3.5. Test Result.....	16
3.6. Test Photograph.....	20

Product Photos: Please refer to the file: 2410697R-Product Photos

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Report No.	Version	Description	Issued Date
2410697R-0E3012150009-A	V1.0	Initial issue of report.	2024-04-17

1. General Information

1.1. EUT Description

Product Name	Network Camera
Trademark	VIVOTEK
Model No.	FD9383-HV, FD833-HV
EUT Max Frequency	2666 MHz
EUT Rated Voltage	PoE 37-57 Vdc
EUT Test Voltage	PoE


Note: The EUT is including two models for different marketing requirement.

1.2. Mode of Operation

DEKRA has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Pre-Test Mode	
Mode 1: Normal Operation, PoE In	
Final Test Mode	
Emission	Mode 1

1.3. Configuration & Details of Tested System



1.4. EUT Exercise Software

1	Setup the EUT and simulators as shown on 1.3.
2	Turn on the power of all equipment.
3	All the features of the EUT operation normally.

2. Technical Test

2.1. Summary of Test Result

- ☒ No deviations from the test standards
☐ Deviations from the test standards as below description:

Emission				
Performed Item	Normative References	Test Performed	Test Site	Verdict
Conducted Emission	ICES-003 Issue 7:2020, Class A ANSI C63.4-2014, ANSI C63.4a-2017 CAN/CSA-CISPR 32:17	No	--	N/A
Radiated Emission	ICES-003 Issue 7:2020, Class A ANSI C63.4-2014, ANSI C63.4a-2017 CAN/CSA-CISPR 32:17	Yes	FS-CB01 FS-CB03	Pass

Note:

1. Test Site information refers to test Laboratory Information.

Test Laboratory:	DEKRA Testing and Certification Co., Ltd. Linkou Laboratory
Address:	No.5-22, Ruishukeng Linkou District, New Taipei City, 24451, Taiwan, R.O.C
Phone number:	+886-2-8601-3788
Fax number:	+886-2-8601-3789
Test Site	
LK:	No.5-22, Ruishukeng Linkou District, New Taipei City, 24451, Taiwan, R.O.C
FS:	No.6, Lane 75, Wenlin St., Linkou Dist., New Taipei City, 244017, Taiwan, R.O.C No. 85, Wenlin St., Linkou Dist., New Taipei City, 244017, Taiwan, R.O.C
HY:	No.26, Huaya 1 st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C

2.2. List of Test Equipment

Radiated Emission (Below 1GHz) / FS-CB01

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Due Date
Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	01124	2023/9/18	2024/9/17
Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	01126	2023/9/18	2024/9/17
EMI Test Receiver	R&S	ESR7	102255	2023/3/27	2024/3/26
EMI Test Receiver	R&S	ESR7	102254	2023/12/7	2024/12/6
Coaxial Cable	SUHNER	SUCOFLEX 106	AC043-SF AC044-SF AC045-SF AC046-SF AC047-SF AC049-SF AC051-SF AC052-SF	2023/7/7	2024/7/6
Preamplifier	SGH	EM330	20200921-5	2023/6/19	2024/6/18
Preamplifier	SGH	EM330	20200921-3	2023/6/19	2024/6/18
NSA	DEKRA	N/A	N/A	2023/7/8	2024/7/7
Test Software version : e3 V9					

Radiated Emission (Above 1GHz) / FS-CB03

Instrument	Manufacturer	Type No.	Serial No.	Cal. Date	Due Date
Double Ridged Guide Horn Antenna	ETS-Lindgren	3117	00240055	2023/12/14	2024/12/13
Horn Antenna	COM-POWER	AH-840	101087	2023/6/30	2024/6/29
EMI Test Receiver	R&S	ESR26	101706	2023/4/24	2024/4/23
Signal Analyzer	R&S	FSV40	101148	2023/5/16	2024/5/15
Coaxial Cable	SUHNER	SUCOFLEX 106	RF003/B	2023/7/5	2024/7/4
Coaxial Cable	SUHNER	SUCOFLEX 106	RF003/C	2023/7/5	2024/7/4
Coaxial Cable	RON SOL	R-Test EW0630	RF003/D	2023/7/5	2024/7/4
Coaxial Cable	RON SOL	MP533A	AC030-MP	2023/7/5	2024/7/4
Microwave Preamplifier	EMCI	EMC051835SE	980311	2023/2/4	2024/2/3
Microwave Preamplifier with cable	EMCI	EMC184045SE	980314	2023/8/30	2024/8/29
VSWR	DEKRA	N/A	N/A	2023/7/4	2024/7/3
Test Software version : e3 V9					

2.3. Measurement Uncertainty

Test Items	Uncertainty
Radiated Emission (Below 1GHz)	± 5.5 dB
Radiated Emission (Above 1GHz)	± 4.7 dB

2.4. Test Environment

Performed Item	Items	Required
Radiated Emission	Temperature (°C)	10-40
	Humidity (%RH)	10-90


3. Radiated Emission

3.1. Test Specification


According to Standard : ICES-003 Issue 7

3.2. Test Setup

Under 1GHz Test Setup:



Above 1GHz Test Setup:



3.3. Limit

Radiated emissions limits (30 MHz to 1 GHz)				
Frequency range (MHz)	Class A (3 m) Quasi-peak (dBuV/m)	Class A (10 m) Quasi-peak (dBuV/m)	Class B (3 m) Quasi-peak (dBuV/m)	Class B (10 m) Quasi-peak (dBuV/m)
30-88	50.0	40.0	40.0	30.0
88-216	54.0	43.5	43.5	33.1
216-230	56.9	46.4	46.0	35.6
230-960	57.0	47.0	47.0	37.0
960-1000	60.0	49.5	54.0	43.5
Note: The more stringent limit applies at transition frequencies.				

Required highest measurement frequency for radiated emissions

Highest internal frequency (F_x)	Highest measured frequency
$F_x \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} < F_x \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} < F_x \leq 1 \text{ GHz}$	5 GHz
$F_x > 1 \text{ GHz}$	$5 \times F_x$ up to a maximum of 40 GHz
Note: F_x is the highest fundamental frequency generated and/or used in the ITE or digital apparatus under test.	

Radiated emission limits at 3 m distance (at and above 1 GHz)				
Frequency range (GHz)	Class A Average dB(uV/m)	Class A) Peak dB(uV/m)	Class B Average dB(uV/m)	Class B Peak dB(uV/m)
1 - F_M	60	80	54	74
<p>Note:</p> <ol style="list-style-type: none"> 1. The highest measurement frequency, F_M, in GHz, shall be determined as per table 3. 2. The measurement bandwidth shall be 1 MHz or greater. 3. These limit levels apply for a measurement distance of 3 m. If using a different measurement distance, the measured levels shall be extrapolated to the 3 m limit distance using a factor of 20 dB per decade of distance. The measurement distance shall place the measurement antenna in the far field of the ITE or digital apparatus under test. 4. The test site shall have been validated at the distance used for radiated emission measurements on the ITE or digital apparatus under test. 				

3.4. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground.

The turn table can rotate 360 degrees to determine the position of the maximum emission level and the antenna (boresight antenna tower) can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated on radiated measurement.


On any frequency or frequencies below or equal to 1000MHz, the radiated limits shown are based on measuring equipment employing a quasi-peak detector function and above 1000MHz, the radiated limits shown are based measuring equipment employing an peak & average detector function.

The measurement distance between the EUT and antenna is 3 meters or 10 meters for under 1GHz and 3 meters for above 1GHz.

The bandwidth below 1GHz setting on the field strength meter (Test Receiver) is 120kHz and above 1GHz is 1MHz.

3.5. Test Result

Model No	FD9383-HV	Site	FS-CB01
Test Voltage	PoE	Test Date	2024-01-25
Test Mode	Mode 1	Engineer	ZhengLam Yap
Polarity	Horizontal	Temperature (°C)	17.8
Test Condition	--	Humidity (%RH)	66.9




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB/m)	Ant Pos (cm)	TT Pos (deg)	Detector Type
1	51.144	15.63	40.00	-24.37	38.43	-22.80	200	87	QP
2	148.072	12.84	43.50	-30.66	35.60	-22.76	400	221	QP
3	216.000	19.15	43.50	-24.35	45.11	-25.96	400	136	QP
4	359.989	20.55	47.00	-26.45	40.64	-20.09	300	207	QP
5	648.016	25.48	47.00	-21.52	38.39	-12.91	400	314	QP
6*	792.020	25.73	47.00	-21.27	35.69	-9.96	400	281	QP

Remark:

1. "*" means this data is the worst margin; "!" means this data is over limit.
2. Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+Cable Loss-Pre Amp).
3. Margin=Emission Level - Limit.

Model No	FD9383-HV	Site	FS-CB01
Test Voltage	PoE	Test Date	2024-01-25
Test Mode	Mode 1	Engineer	ZhengLam Yap
Polarity	Vertical	Temperature (°C)	17.8
Test Condition	--	Humidity (%RH)	66.9




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB/m)	Ant Pos (cm)	TT Pos (deg)	Detector Type
1*	51.069	32.57	40.00	-7.43	54.83	-22.26	100	1	QP
2	216.008	25.78	46.40	-20.62	51.01	-25.23	100	213	QP
3	360.003	27.40	47.00	-19.60	46.91	-19.52	100	324	QP
4	647.999	33.70	47.00	-13.30	45.96	-12.26	300	238	QP
5	792.014	34.36	47.00	-12.64	43.87	-9.51	200	248	QP
6	935.995	26.60	47.00	-20.40	33.76	-7.17	100	285	QP

Remark:

1. "*" means this data is the worst margin; "!" means this data is over limit.
2. Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+Cable Loss-Pre Amp).
3. Margin=Emission Level - Limit.

Model No	FD9383-HV	Site	FS-CB03
Test Voltage	PoE	Test Date	2024-01-25
Test Mode	Mode 1	Engineer	Chris Hu
Polarity	Horizontal	Temperature (°C)	21.6
Test Condition	--	Humidity (%RH)	53.7




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB/m)	Ant Pos (cm)	TT Pos (deg)	Detector Type
1	3996.250	48.38	80.00	-31.62	48.52	-0.14	200	33	Peak
2	10600.750	48.51	80.00	-31.49	40.16	8.35	200	291	Peak
3*	12900.000	49.77	80.00	-30.23	38.11	11.66	136	360	Peak

Remark:

1. "*" means this data is the worst margin;"!" means this data is over limit.
2. Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+Cable Loss-Pre Amp).
3. Margin=Emission Level - Limit.
4. The above 1 GHz test. When PEAK measures level less than AV limit by 20 dBuV, its average is not measured separately.

Model No	FD9383-HV	Site	FS-CB03
Test Voltage	PoE	Test Date	2024-01-25
Test Mode	Mode 1	Engineer	Chris Hu
Polarity	Vertical	Temperature (°C)	21.6
Test Condition	--	Humidity (%RH)	53.7



No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB/m)	Ant Pos (cm)	TT Pos (deg)	Detector Type
1	2666.000	47.65	80.00	-32.35	50.83	-3.18	200	268	Peak
2	3996.250	48.41	80.00	-31.59	48.55	-0.14	200	84	Peak
3*	12381.500	50.41	80.00	-29.59	39.36	11.05	100	360	Peak

Remark:

1. "*" means this data is the worst margin; "!" means this data is over limit.
2. Emission Level=Reading Level + Correct Factor(Correct Factor=Ant Factor+Cable Loss-Pre Amp).
3. Margin=Emission Level - Limit.
4. The above 1 GHz test. When PEAK measures level less than AV limit by 20 dBuV, its average is not measured separately.

3.6. Test Photograph

Test Mode : Mode 1

Description : Front View of Radiated Test



Test Mode : Mode 1

Description : Back View of Radiated Test



Test Mode : Mode 1

Description : Front View of High Frequency Radiated Test

